

DATA CENTER 4 TECH SITE SPECS



ENVIRONMENTAL CONTROL

CEU Quantity	(3) Outside Pad Units
Total BTU	150 Tons
Cooling Type	Direct Expansion (DX)
Redundancy	N+1

POWER

Power Options	120VAC, 208VAC, 3-Phase, -48VDC
UPS	(1) Toshiba , (2) Liebert Units
Sizes	(2) 100kVa, 500kVa
Redundancy	N+1
Harmonic Filters	Yes
Battery Type	GNB Lead-acid

Battery Life at Full Load	10 Minutes
Generator	(1) Caterpillar, (1) Detroit
Generator Sizes	750kVa, 500kVa
Generator Fuel	(2) Diesel; Priority Fuel Agreement
Remotely Monitored	Yes

SECURITY

CCTV	Yes, Exterior/Interior
CCTV Recorder	Up to 90 Days
Card Access	HID Proximity Card
Access Control	Keypad Access to Site

FIRE PROTECTION

Type	ECARO-25 Gas
Number of Zones	2
Smoke/Heat Detection	VESDA
Remotely Monitored	Yes

CARRIERS

● On-site ○ Accessible

123NET	●	Lumen	○
ACD	●	MetroNet	○
AT&T	●	ManagedWay	●
Clear Rate Comm	○	Merit	●
CMS Internet	○	STELLAR Broadband	○
Cogent	●	TeliaSonera	○
Comcast	●	US Signal	●
Crown Castle	○	Verizon	○
D&P	○	Windstream	●
DayStarr	○	WOW!	○
Everstream	●	Zayo	○

UPSTREAM PROVIDERS

Lumen	AS209	Chicago, IL
Cogent	AS174	Southfield, MI
GTT	AS3257	Southfield, MI
Hurricane Electric	AS6939	Southfield, MI
Lumen	AS3356	Southfield, MI
NTT Communications	AS2914	Chicago, IL
Tata Communications	AS6453	Ashburn, VA
TeliaSonera	AS1299	Southfield, MI
Zayo	AS6461	Southfield, MI

PEERING LOCATIONS

DET-IX	Detroit, MI
Equinix Chicago	Chicago, IL
Equinix Ashburn	Ashburn, VA

SUPPORT - 24/7/365

Smart Hands	15 Minute Response Time
Support	----

LOCATION & SITE INFORMATION

Address	400 76th Street SW Suite 12 Byron Center, MI 49315
Colocation Space	4,300 Sq. Ft.
Floor Type	Slab
Loading Area	Street Level

SITE STRUCTURE

Completed	2012
Number of Floors	1
Ceiling Clearance	10 ft.
Floor Load	150 psf.
Structure Type	Structural Steel, Brick Trim
Exterior Type	Steel
In Flood Plain	No

SITE UTILITY

Electricity Provider	Consumers
Available Utility Power	1MW

COMMUNICATION

NPA-NXX	616-878
# of Entrance Vaults	2